

ECLIPSE 2 ELiTE[®]

LITHIUM WALK-BEHIND REEL MOWER

EXPERIENCE AN ELiTE[®] CUT

The Eclipse 2 ELiTE is where cutting edge lithium technology meets pristine cuts, allowing you to experience seamless operation and superior results. Compromise nothing with a programmable frequency of clip, floating head, onboard controller, and 40% less vibration than internal combustion engines. A low-profile design improves visibility to the floating cutting head and includes an onboard controller for maximum management.



VIRTUALLY SILENT CUTTING

VERTICUTTING CAPABILITIES

COMPATIBLE WITH ALL ECLIPSE 2 ACCESSORIES

CUT WIDTH

**18" 22"
OR 26"**
(45.7CM, 55.9CM
OR 66CM)

CUT HEIGHT

**0.062"-
0.438"**
(1.57MM - 11.13MM)

BLADES PER REEL

**7, 11
OR 15**
AVAILABLE

MOWER POWER

**SAMSUNG
50AH**
LITHIUM BATTERY



Actual operating power output may vary due to conditions of specific use. Run time will vary based on conditions of specific use, accessories, and terrain. NOTE: Specifications, while correct at time of printing, may change without notice. © 2025 Textron Specialized Vehicles Inc. 10037-G1 (Rev. 01/2025)

ECLIPSE 2 ELITE

LITHIUM WALK-BEHIND REEL MOWER



Personalize the all-electric walking mower with countless accessory options, like reels, rollers, bedknife options, verticutter, groomer, fine bristle brush, and magknife.



With zero fumes and hydraulics, the electric powertrain leaves no marks behind.



Featuring a traction drum and front roller that carry the full weight of the mower and basket, ensuring the cutting head is allowed to fully float, unaffected by the weight of the mower or grass basket.



REELS & BLADES

BLADE MATERIAL	Hardened, high manganese carbon steel
REEL SPEED	Electronically controlled, 2200 rpm maximum
FREQUENCY OF CLIP	Programmable electronically controlled Frequency of Clip based on actual machine speed

TRACTION, BRAKES & SPEED

MOWER DRIVE SYSTEM	Samsung SDI Lithium Battery
TRACTION DRIVE	7.75" (19.68cm) diameter machine smoothed aluminum drum driven via a brushless DC motor and synchronous belt
OPERATOR PRESENCE CONTROL	Standard InCommand™ operator controls (Traction and Reel) with integrated Operator Presence Control
DIFFERENTIAL	Full automotive type, housed in traction drum
TRACTION DRUM	7.75" (19.68cm) diameter smooth machined aluminum
BRAKES	Lever actuated hub brake with parking lock
MOWING SPEED	Electronically controlled and programable 0-3.8 mph (6.12 km/h) max

WEIGHTS & DIMENSIONS

WEIGHT	18": 213lb (97kg), 22": 229lb (104kg), 18" floating head: 248lb (113kg), 22" floating head: 252lb (114kg) (all weights are with catcher, grooved steel roller and kickstand)
--------	--

ACCESSORIES

- Turf Groomer
- Verticut
- Bi-directional groomer / Brush
- LED light kit
- Mower Caddy Trailer
- Push Brush Attachment
- Transport wheels



For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

