

ECLIPSE 360 ELITE[®]

LITHIUM RIDE-ON REEL MOWER

THE ELITE GREENS CHOICE

The Eclipse 360[®] ELITE doesn't just meet expectations - it challenges you to redefine yours. With industry-leading quality of cut and performance, this machine is setting the new standard for efficiency through sustainable advantages, including a 45% reduction in vibrations and an 85-decibel rating to the operators ear, eliminating the need for hearing protection.



CONSISTENT FREQUENCY OF CUT

NO BATTERY MAINTENANCE OR HYDRAULIC OIL

SIGNIFICANT OPERATIONAL COST SAVINGS

CUT WIDTH

62"
(1.6M)

BATTERY PACK

250AH
LITHIUM

BLADES PER REEL

7, 9, 11
OR 15

RUN TIME

UP TO **50+**
GREENS ON A
SINGLE CHARGE

CUT HEIGHT

0.062"-
0.438"
(1.6MM - 11.1MM)

CUTTING CAPACITY

143K
SQ. FT.
(12,449 SQ. M.)



JACOBSEN

Actual operating power output may vary due to conditions of specific use. Run time will vary based on conditions of specific use, accessories, and terrain. NOTE: Specifications, while correct at time of printing, may change without notice. © 2025 Textron Specialized Vehicles Inc. 10025-G3 (Rev. 01/2025)

ECLIPSE 360 ELITE™

LITHIUM RIDE-ON REEL MOWER



Unique swing out center unit engineered for easy maintenance, cleaning, or swapping of the unit.



The 250Ah (13kWh) lithium battery pack, powered by Samsung SDI technology, has the capacity to mow your greens for multiple days without the need for daily recharging.



Experience the durability and precision of Classic XP Reels with TrueSet. These reels feature a rugged welded frame that offer a choice of smooth, grooved, steel, or aluminum rollers.



REELS & BLADES

NUMBER AND SIZE	3 x 22" (55.88cm) reels; 5" (12.7cm) diameter
CUTTING WIDTH	62" (1.6m)
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	New long life linear actuator
CUTTING FREQUENCY	0.036" - 0.250" (0.91 mm - 6.35 mm) with 15 blade reel, electronically adjustable

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Front / 2WD - AC; 4.4HP (3.3kW) continuous (Optional 3WD - PM; 3.2HP (2.4kW))
REEL DRIVE	One brushless DC motor per reel; 1.3HP (0.97kW) continuous
HYDRAULIC SYSTEM	No hydraulic oil
SERVICE BRAKES	Dynamic regenerative braking system
PARKING BRAKES	Automatic electro-magnetic multi-plate
STEERING	Variable ratio Drive-by-wire steering with feedback control
MOWING SPEED	0 - 5.0mph (0 - 8.9km/h); electronically adjustable max speed
TRANSPORT SPEED	0 - 9.0mph (0 - 14.5km/h); electronically adjustable max speed
TIRES	18 x 10.5 x 8 4-ply

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	1,598lb (725kg) with groomers, rear roller brushes, grass boxes and 15 blade reels, charger and aluminum front rollers
LENGTH	101" (2.56m) with catchers
OVERALL HEIGHT (including ROPS)	79.3" (2.01m)
WHEELBASE	52" (1.32m)
TRANSPORT/WORKING WIDTH	67.7" (1.72m)

WARRANTY

MOWER WARRANTY	2 Year Machine & 5 Year Battery
----------------	---------------------------------

ACCESSORIES

- Turf Groomer: 22" (55.9 cm) width and 0.25" (6.3mm) or 0.50" (12.7mm) spacing
- Spiker
- Powered rear roller cleaning brush
- High cut kit - 15/16" 2.4 cm when used with 2 3/16" roller
- Premium seat - grammar seat in grey vinyl with suspension base, adjustable brackets
- ROPS mounted LED light kit
- Dew whip holder
- Canopy / sunshade kit - adjustable
- Tow bar
- Traction tire assembly 18 x 9.5 x 8 (wheel and tire)
- Turf brushing groomer
- Bi-directional groomers and brushes 3WD kit

ROLLERS

- 22" (55.9 cm) Grooved assembly steel disk roller - 2" (5.1 cm) dia.
- 22" (55.9 cm) Grooved segmented machined aluminum roller - 2 1/4" (5.7 cm) dia.
- 22" (55.9 cm) Solid tube steel roller with scraper (light duty) - 2" (5.1 cm) dia.
- 22" (55.9 cm) Solid tube steel roller with scraper (heavy duty) - 2" (5.1 cm) dia.
- 22" (55.9 cm) Grooved machined steel roller - 2 3/16" (5.6 cm) dia.
- 22" (55.9 cm) Grooved machined aluminum roller - 2 3/16" (5.6 cm) dia.



For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

