

F305

HIGH CAPACITY WIDE AREA
REEL MOWER

ENGINEERED FOR PRODUCTIVITY AND STABILITY

The F305 delivers on reliability and unsurpassed productivity with the innovative SureTrac™ system and enhanced operator controls. Equipped with a 44.9HP Kubota® Stage V diesel engine, it ensures top-notch performance and enhanced cutting capabilities. This machine can cover 10.67 acres per hour at 7.5mph, ensuring it is a partner from start to finish.



EASE OF SERVICE

HIGH CUTTING CAPACITY

DELUXE OPERATOR COMFORT

CUT WIDTH

116"
(2.94M)

CUT HEIGHT

**0.47" -
1.85"**
(12MM - 47MM)

CUTTING CAPACITY

10.67^{AC}
(4.32HA) / HR
AT 7.5MPH (12KM/H)

FUEL CAPACITY

9.98^{GAL}
(45.4L)

MOWER ENGINE

**KUBOTA
44.9HP**
(33KW) DIESEL

DRIVE SYSTEM

**HYDROSTATIC
-SERVO
CONTROLLED**



JACOBSEN

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10027-G2 (Rev. 01/2025)

F305

POWERFUL WIDE AREA REEL MOWER



The F305's hydraulic system is fitted with a system capacity of 8.31 gallons, ensuring smooth and reliable operation.



This wide area mower has a cutting width of 116-inches with five 26-inch durable cutting units so it can reach even the largest of areas.



4WD comes as standard allowing for greater traction and a light touch on fine sports turf.

305



REELS AND BLADES

CUTTING UNITS	26" (66.4 cm) cylinder, 6.5" (165 mm) diameter floating head cutting unit (5 required)
NUMBER AND SIZE	7 or 11 blade cutting head units, 46 cuts per meter at 7.5 mph (12 kph)
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	Wing units can be raised individually for transport

TRACTION, BRAKES & SPEED

TRACTION DRIVE	SureTrac™ Traction System with full-time four wheel drive in forward and reverse, parallel cross series system for excellent grip and a light touch
CUTTING UNIT DRIVE	Fixed displacement hydraulic motors directly coupled to cutting unit
HYDRAULIC SYSTEM	8.31 gal (37.8L) capacity; Grade of oil to A.P.I. Classification CE/SF grades SAE 10W-30
SERVICE BRAKES	Hydrostatic braking
PARKING BRAKES	Zero-maintenance wet parking brakes
STEERING	Hydrostatic power steering with adjustable tilt steering wheel
MOWING SPEED	Selectable up to 7.5mph (12km/h)
TRANSPORT SPEED	Selectable up to 8.7mph (14km/h)
REVERSE SPEED	Selectable up to 4mph (6.4km/h)

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	3450lbs (1565Kg)
WEIGHT TRANSFER	Hydraulically adjustable weight transfer to boost traction
LENGTH	116" (2.95m)
OVERALL HEIGHT	85" (2.15m)
WHEEL BASE	65" (1.65m)
TRANSPORT WIDTH	99.2" (2.52m)
WORKING WIDTH	130" (3.31m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- 26" (66cm) powered rear cleaning brush factory fitted or for field fitting
- Grass catchers
- LED working light kit
- Grammer air suspension seat
- Sun canopy



For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

