

GP400 GAS/DIESEL

VERSATILE RIDE-ON REEL MOWER

ELEVATING GREENS MAINTENANCE

The GP400 is tailored to provide Jacobsen's leading quality of cut to greens, tees and surrounds. With a swing out center unit, it allows for ease of service, and comes complete with onboard backlapping to ensure the mower is ready from start to finish. This machine comes with the choice of a 17.7 HP Briggs and Stratton Vanguard V-Twin gas engine or a 18.8HP Kubota 3-cylinder diesel engine. The GP400 makes turf management easier.



ADJUSTABLE REEL DROP AND REEL SEQUENCE

ADJUSTABLE HEIGHT OF CUT:
0.062 - 0.438" (1.6 - 11.1MM)

OPTIONAL 3WD

CUT WIDTH

62"
(1.6M)

CUT HEIGHT

0.062" - 0.438"
(1.6MM - 11.1MM)

CUTTING CAPACITY

2.37 AC
(0.96HA) / HR
(1.6M X 6KM/HR)

FUEL CAPACITY

15 GAL
(58.6L)

MOWER ENGINE
KUBOTA

17.7HP
(13.2KW) GAS
BRIGGS & STRATTON
18.8HP
(13.8KW) DIESEL

BLADES PER REEL

**7, 9, 11
OR 15**



Actual operating power output may vary due to conditions of specific use. Run time will vary based on conditions of specific use, accessories, and terrain. NOTE: Specifications, while correct at time of printing, may change without notice. © 2025 Textron Specialized Vehicles Inc. 10040-G1 (Rev. 01/2025)

GP400 GAS/DIESEL

VERSATILE RIDE-ON REEL MOWER



The GP400 has a biodegradable hydraulic fluid system, which reduces the impact of leaks and spills on the turf.



This machine features an ergonomically designed dash panel incorporating joystick controls for easy and simple operation.



Offered with a range of reels and blades to meet your application, the GP400 also features reel drop sequencing for complete control.

400



REELS & BLADES		
NUMBER AND SIZE	3 x 22" (55.88cm) reels; 5" (12.7cm) diameter	
BLADE MATERIAL	Hardened high carbon steel	
CUTTING UNIT LIFT	Hydraulic double action cylinders; parallel link head leveling system	
CUTTING FREQUENCY	7 Blade: 0.079"/mph (1.24mm/km/h), 15 Blade: 0.037"/mph (0.58mm/km/h)	
TRACTION, BRAKES & SPEED		
TRACTION DRIVE	Hydraulic motor on each drive wheel, optional 3WD	
REEL DRIVE	Gear-type hydraulic motor; backlap control valve standard	
HYDRAULIC SYSTEM	8gal. (25.7 L) capacity; 10 micron, full- Flow Filtration; biodegradable hydraulic fluid; oil cooler standard	
SERVICE BRAKES	Hydrostatic braking	
PARKING BRAKES	6" (152mm) caliper disc, hand operated	
STEERING	Power Steering	
MOWING SPEED	3.7mph (6km/h)	
TRANSPORT SPEED	0 - 7.5mph (0 - 12km/h)	
WEIGHTS & DIMENSIONS		
	GAS	DIESEL
WEIGHT (excluding fuel)	1235 - 1578 lbs. (560 - 716.3 kg)	1388 - 1746lb (630 - 792kg)
LENGTH	83" (2.12m)	
OVERALL HEIGHT (ROPS up)	67.7" (1.72m)	
WHEELBASE	51.2" (1.30m)	
TRANSPORT WIDTH	74.5" (1.89m)	
WORKING WIDTH	74.5" (1.89m)	
WARRANTY		
MOWER WARRANTY	2 Years	

ACCESSORIES

- 55.9cm (22") Front rollers ranging from 5.1cm (2") to 5.7cm (2½") - solid tube steel, grooved assembled or machined aluminum or steel
- Grass catcher kit (new Eclipse style)
- Turf Groomer®
- Quick roll greens roller (set of 3)
- Spiker attachment w/ frame assembly
- 22" (55.9cm) front roller fine bristle brush
- Powered rear roller brush for 12.7 x 55.9cm (5" x 22") cutting unit
- High cut kit - 2.4cm (1⅝") when used with .5cm (⅜") roller
- GP400 3WD kit
- Automatic mow speed selection kit



For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

