

HR600

LARGE AREA ROTARY MOWER

PRECISION AND POWER IN EVERY TURN

The HR600 is a robust machine built on a narrow platform for effortless 180-degree turns, leaving no blade of grass uncut. With easy engine access, a reversing engine fan, and maintenance-free wet parking brakes, it ensures reliability and efficiency. Experience unmatched operator comfort and cutting-edge technology that guarantees effortless mowing, making the HR600 the ultimate solution for achieving a first-class finish.



65" (1.67M) TRANSPORT WIDTH

CAB WITH A/C AVAILABLE

TILT SENSORY TECHNOLOGY

CUT WIDTH

137"
(3.5M)

CUT HEIGHT

1"- 4.75"
(25MM -121MM)
0.25" (6.4MM)
INCREMENTS

CUTTING CAPACITY

13.8^{AC}
(5.6HA) / HR
AT 10MPH (16KM/H)

FUEL CAPACITY

20.4^{GAL}
(77.1L)

MOWER ENGINE

KUBOTA[®]
65.2HP
(18.6KW) TURBODIESEL

TRANSPORT SPEED

15.5^{MPH}
(25KPH)



JACOBSEN

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10031-G2 (Rev. 01/2025)

HR600

LARGE AREA ROTARY MOWER



Powered by an engine that matches the machine's need for power, the HR600 boasts of a Kubota 4-cylinder turbo diesel engine that delivers 65.2 HP.



The HR600 is designed for efficiency and agility so it can cover up to 13.8 acres in an hour, making it ideal for large areas.



For those seeking additional comfort, an optional climate-controlled cab offers superior visibility with a heated windshield, reduced noise, and premium air suspension seating.



DECKS & CUTTING UNITS

NUMBER AND SIZE	1 x 60" (1.52m) front deck; 2 x 44" (1.12m) wing units
BLADE MATERIAL	MARBAIN® boron alloy steel
DECK LIFT & LOWER	Individual via fingertip operated joysticks
WEIGHT TRANSFER	On demand electrically operated hydraulic weight transfer system
DECK CONSTRUCTION	11 gauge (3mm) Strenx, high strength steel shell

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Hydrostatic closed loop parallel-cross-series SureTrac™ system
DECK DRIVE	Seven individual hydraulic motors with self lubricating integral bearings
HYDRAULIC SYSTEM	13.3 gal. (50.2L) reservoir with 10 micron remote charge filters and suction screening at tank. Oil cooler in side by side radiator.
SERVICE BRAKES	Dynamic through hydrostatic traction system
PARKING BRAKES	Automatic wet parking brakes integrated into wheel motors
STEERING	Power Steering
MOWING SPEED	10mph (16.4km/h)
REVERSE SPEED	4mph (6.4km/h)
TIRES	Front Tires: 26 x 12-12 tubeless 8 ply. Rear Tyres :20 x 10-8 tubeless 6 ply

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	3873 lbs (1756kg) with ROPS, 4356 lbs. (1976kg) with cab
LENGTH (less catchers)	143" (3.62m) front deck down
OVERALL HEIGHT (ROPS up)	83" (2.1m)
WHEELBASE	64" (1.65m)
TRANSPORT WIDTH	65" (1.67m)
WORKING WIDTH	143" (3.63m)

FLUID CAPACITIES	Coolant Sytem and Capacity: Side-by-side radiator/hydraulic oil cooler; pressurized; 2 gal. (7.6 L) capacity, 8.5 fins per inch
------------------	---

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- Road light kit
- Canopy/sunshade
- Climate controlled cab
- Cab accessories - road light kit, Rear wiper kit



For information and support:

www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

