

LF570

HIGH PERFORMANCE RIDE-ON
REEL MOWER

UNMATCHED PRECISION USING JACOBSEN'S CUTTING-EDGE TECHNOLOGY

Meet all large turfcare needs with the LF570. This high performance reel mower features our SureTrac™ parallel-cross-series traction system for superior traction on hills and side slopes, and FlashAttach™ for quick and easy replacement of reel motors. Powered by a diesel Kubota® engine with either 37.5HP or 50.2HP, this machine can be trusted to tackle any job it's tasked with.



ADJUSTABLE HEIGHT OF CUT:
0.375-1.125"

ONBOARD DIAGNOSTICS

SEMI-AUTOMATIC WET
PARKING BRAKES

CUT WIDTH

100"
(2.54M)

ERGONOMICS

PROGRAMMABLE
**SPEED
CONTROL**

CUTTING CAPACITY

UP TO **8** AC
(3.24HA) / HR
AT 8MPH (12.9KM/H)

CUTTING REELS

5" (12.7CM) OR
7" (17.78CM)

MOWER ENGINE

KUBOTA
37.5
/50.2HP
(28/37.4KW) DIESEL

TRANSPORT SPEED

12 MPH
(19.3KPH)



JACOBSEN

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10038-G1 (Rev. 01/2025)

LF570

HIGH PERFORMANCE RIDE-ON REEL MOWER



The LF570 features a wet braking system integrated in the front wheel motors. These brakes eliminate the need for regular brake maintenance and extends the machine's lifespan.



Superior cutting capacity with up to 8 acres per hour at 8mph, ensure maximum productivity to get the job done.



Equipped with an impressive cutting width of 100-inches (2.54m), this machine is more than capable of mowing large areas efficiently.



570

DECKS & CUTTING UNITS

NUMBER AND SIZE	9 or 11 heavy section fairway blades
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	Hand operated, joystick controlled hydraulic lift system, one-touch lift/lower control for all reel

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Variable displacement, electronically controlled hydrostatic drive; 4WD models: SureTrac™ parallel-cross-series traction system, four high-torque wheel motors, 2WD in reverse.
REEL DRIVE	Fixed displacement hydraulic motors with FlashAttach quick disconnect coupled reel motors. Standard on-board backlapping.
HYDRAULIC SYSTEM	114 gal. (53L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic braking through traction system
PARKING BRAKES	Semi-automatic, wet parking brakes integrated in front wheel motors
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	Up to 8mph (13kph)/ T4I: Up to 11mph (19kph)
REVERSE SPEED	Selectable up to 5mph (8km/h)

WEIGHTS & DIMENSIONS

	2WD	4WD
WEIGHT (excluding fuel)	3,221 lbs. (1,461 kg) 2WD High HP: 3,467 lbs. (1,573 kg)	3,552 lbs. (1,611 kg) 4WD High HP: 3,798 lbs. (1,723 kg) / T4I: 4WD: 2642 lbs. (1199kg)
LENGTH (less catchers)	108" (2.74m)	
OVERALL HEIGHT (ROPS up)	88" (2.23m)	
WHEELBASE	58" (1.5m)	
TRANSPORT WIDTH	87" (2.2m)	
WORKING WIDTH	115" (2.92m)	

WARRANTY

MOWER WARRANTY	2 years
----------------	---------

ACCESSORIES

- 55.9cm (22") Front rollers ranging from 5.1cm (2") to 7.6cm (3") - solid tube steel, grooved assembled or machined aluminum or steel
- Turf Groomer®
- Powered rear roller cleaning brush
- Canopy/Sunshade
- Grass Catcher
- High-cut kit
- Premium air suspension seat
- LED operator platform light kit
- Hood locking latch (required for CE)
- Verticut reels



For information and support:

www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

