

PGM22

LIGHTWEIGHT WALK-BEHIND
REEL MOWER

LIGHTWEIGHT PRECISION IN EVERY PASS

The PGM22 is built for simplicity and dependability. Trusted by generations to deliver Jacobsen's industry-leading quality of cut, this machine features InCommand™ operator controls with an ergonomic D-handle, variable speed control, and operator presence control. Engineered with a centrifugal clutch and hardened steel blades, the PGM22 is durable and long-lasting, making it the right choice for all greens maintenance.

* Engine power is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.



PROFESSIONAL LEVEL OF CUT FOR FINE TURF SURFACES	INCOMMAND OPERATOR CONTROLS FOR ENHANCED	DURABLE CONSTRUCTION WITH HARDENED STEEL BLADES
---	---	--

CUT WIDTH

22"
(55.9CM)

CUT HEIGHT

**.062"-
0.438"**
(1.6MM -11.11MM)

BLADES PER REEL

**11
OR 15**

FUEL CAPACITY

0.66^{GAL}
(2.5L)

MOWER ENGINE

**HONDA
GX-120**
GAS ENGINE

MOWER POWER*

4HP
(2.9KW)



Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10012-G5 (Rev. 01/2025)

PGM22

LIGHTWEIGHT WALK-BEHIND REEL MOWER



Powered by a Honda GX-120 single cylinder gas engine, the PGM22 ensures reliable performance and fuel efficiency.



One of the lightest mowers in its class, this machine is easier to maneuver and reduces turf compaction.



The PGM22 offers a range of optional accessories to allow for a tailored maintenance experience based on individual turf conditions.



REELS & BLADES

BLADE MATERIAL	Hardened, high manganese carbon steel
REEL SPEED	Dependent on Engine RPM and 2.25:1 reel reduction ratio
REAL BEARINGS	Spring-loaded, tapered roller
REEL DIAMETER	5" (127 mm)
FREQUENCY OF CLIP	15 blade: .150" (5.2 mm)
SIDE FRAME MATERIAL	Cast-aluminum alloy

TRACTION, BRAKES & SPEED

MOWER DRIVE SYSTEM	Centrifugal. Drive Clutch
TRACTION DRIVE	Chain Drive
TRACTION REDUCTION RATIO	24:1
OPERATOR PRESENCE CONTROL	Standard InCommand™ operator controls (Traction and Reel) with integrated Operator Presence Control
DIFFERENTIAL	Full automotive type, housed in traction drum
TRACTION DRUM	7.75" (19.68cm) diameter smooth machined aluminum
BRAKES	Lever actuated hub brake with parking lock
TRANSPORT WHEELS	2 x Pneumatic 11" x 4" (27.94cm x 10cm)
MAXIMUM TORQUE	5.4 ft. lbs (7.5Nm)
MOWING SPEED	Dependent on Engine RPM 3.2mph (5.14km/h) max

WEIGHTS & DIMENSIONS

WEIGHT	11 blade reel: 184lb (83.4kg), 15 blade reel: 194lb (88kg) (with Catcher, grooved steel roller and kickstand)
--------	---

SOUND LEVEL

MOWER SOUND LEVEL	95 dBA
-------------------	--------

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- Front rollers
- Verticutters
- Turf groomers for three-dimensional mowing
- LED light kit
- Mower caddy
- Full line of accessories



For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

