SLF530

SUPER-LIGHTWEIGHT REEL MOWER

THE LIGHTWEIGHT SOLUTION FOR SUPERIOR MOWING

This super light weight reel mower sets the standard for advanced precision and performance. The SLF530 leaves turf cut to perfection every time with a wide cutting deck and its lightweight design. With less than 10 PSI ground pressure, this machine is ideal for use on golf fairways and sports fields creating the ultimate operator experience.



LESS GROUND PRESSURE Than a golfer's foot

SUPERIOR MANEUVERABILITY

ONE-TOUCH HYDRAULIC LIFT SYSTEM FOR INCREASED FLEXIBILITY

CUT WIDTH

82⁷⁷ (2.08M)

CUT HEIGHT

.30⁷⁷-0.70⁷⁷ (7.62MM - 17.8MM) **CUTTING CAPACITY**

6.5_{AC} (2.63HA) / HR NO OVERLAPS/STOPS

CUTTING REELS

5X5⁷⁷(12.7CM) DIAMETER X18 REELS **ENGINE**

24.8_{HP} 18.5KW) DIESEL

DRIVE

3_{OR}4 WHEEL DRIVE







Powered by a robust 24.8HP Kubota diesel engine, this gas powertrain delivers consistent, reliable



The SLF530 is available in both 3- and 4-wheel drive. The 3-wheel drive model contains a parallel series for exceptional maneuverability and the 4-wheel offers pure parallel system for superior traction and



Equipped with five 5-inch diameter reels as standard, these reels are available in 8 or 11



blade configurations for maximum customization.		
REELS AND BLADES		
NUMBER AND SIZE	8 or 11 Blade Fairway reel (greens reel cylinders can be installed for custom applications)	
BLADE MATERIAL	Hardened, high manganese carbon steel	
CUTTING UNIT LIFT	Hand operated, joystick controlled hydraulic lift system, one-touch lift/lower control for all reels	
TRACTION, BRAKES & SPEED		
TRACTION DRIVE	3WD: Parallel series 3-wheel drive, 2-wheel drive in reverse. 4WD: Pure Parallel 4-wheel system with selectable 2 or 4-wheel drive and automatic 2-wheel drive in reverse	
REEL DRIVE	Fixed displacement hydraulic motors	
HYDRAULIC SYSTEM	10 micron remote charge filtration, suction screen at tank, oil cooler, side by side radiator	
SERVICE BRAKES	Hydrostatic braking	
PARKING BRAKES	Wet parking brakes integrated into wheel motors	
STEERING	Hydrostatic powered equal displacement cylinder to rear wheels	
MOWING SPEED	6.2mph (10km/h)	
REVERSE SPEED	3.7mph (6km/h)	
WEIGHTS & DIMENSIONS	3WD	4WD
WEIGHT (excluding fuel)	1956lb (887.2kg)	2053lb (931.2kg)
LENGTH (less catchers)	102" (2.59m)	
OVERALL HEIGHT (ROPS up)	83.2" (2.11m)	
WHEELBASE	61.3" (156cm)	62" (157cm)
TRANSPORT WIDTH	96.7" (2.46m)	
WORKING WIDTH	82" (2.08m)	
WARRANTY		
MOWER WARRANTY	2 years	

ACCESSORIES

- Bi-directional turf groomer / brush
- Grass boxes
- Verticutters
- Powered rear roller brushes
- High height of cut kit
- Canopy
- Inclinometer
- Foot rest
- Treaded tires

