

TR320

HIGH TRACTION CONTOUR TRIM
MOWER

TRIM ANYWHERE WITH CONFIDENCE

This highly maneuverable mower is proven to perform no matter the conditions. The TR320 is equipped with advanced contour-following technology that allows the cutting units to independently float and follow the undulations of the terrain. Powered by a Kubota® 24.8 HP diesel engine which is more than capable of handling various mowing conditions, this machine has been designed with the user in mind.



TRAVERSE ENGINE FOR
ENHANCED STABILITY

65.5" (1.66M) TRANSPORT WIDTH

ADJUSTABLE HEIGHT OF CUT: 0.37 - 2.75"
(9.5 - 69.8MM)

CUT WIDTH

72" (1.83M)
OR **84"** (1.83M)
FEATURING ADAPTISHIFT™ WITH
UP TO 12" (30.5CM) OF OFFSET

CUT HEIGHT

0.37"-
2.75"
(9.5MM - 69.8MM)

CUTTING CAPACITY

4.5-5.3^{AC}
(1.83 - 2.13HA) / HR
(1.83-2.13M X 10KM /HR)

FUEL CAPACITY

7.6^{GAL}
(28.7L)

MOWER ENGINE

24.8HP
(18.6KW) DIESEL

BLADES PER REEL

5,7
OR **11**



JACOBSEN

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10043-61 (Rev. 01/2025)

TR320


HIGH TRACTION SIDE SHIFTING TRIM MOWER



The TR320 features hydraulic power steering to enhance maneuverability and operator comfort.



With wet parking brakes that are completely maintenance-free, the TR320 eliminates the need for regular brake maintenance.



With wet parking brakes that are completely maintenance-free, the TR320 eliminates the need for regular brake maintenance.



320

DECKS & CUTTING UNITS

NUMBER AND SIZE	3 x 26" (66.0 cm) or 30" (76.2 cm) reels; 7" (178 mm) diameter
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	Armrest mounted switch
CUTTING FREQUENCY	-

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Parallel-series "on demand" 3WD
REEL DRIVE	Fixed displacement hydraulic
HYDRAULIC SYSTEM	8.7 gal. (33 L) capacity, full flow filtration (10 micron filter); GreensCare biodegradable oil
SERVICE BRAKES	Dynamic braking through hydrostatic drive
PARKING BRAKES	Service-free electronic wet disc
STEERING	Hydraulic power steering with tilt wheel
MOWING SPEED	6.2mph (10km/h)
TRANSPORT SPEED	8.7mph (14km/h)

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	1647 - 2281 lbs. (747 - 1035 kg)
LENGTH	97" (2.46m)
OVERALL HEIGHT (including ROPS)	80" (2.04m)
WHEELBASE	43.5" (1.36m)
TRANSPORT WIDTH	65.5" (1.66 m)
WORKING WIDTH	83" (2.11m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- Slick tires
- Verticutting reels
- Grass baskets
- Light kit
- Backlap kit
- Canopy
- Weight transfer kit



For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

