

TR330

HIGH TRACTION SIDE SHIFTING
TRIM MOWER

CONFIDENCE IN EVERY CUT WITH SIDE SHIFTING TECHNOLOGY

The TR330 has the ability to trim around bunkers, ponds, lakes, and other hazards with ease. Using AdaptiShift™ technology, the side shifting reel allows the operator to move cutting reels up to 18-inches to either side, enabling precise trimming around any area. Adjustable cutting width allows for dependability to tackle the area being maintained, and a trustworthy engine for long-lasting power makes the TR330 the perfect choice for reaching every blade of grass.



TRAVERSE ENGINE FOR
ENHANCED STABILITY

FLEXIBLE WORKING
ENVIRONMENT

3WD TRACTION
SYSTEM

CUT WIDTH

72" (1.83M)
OR **84"** (1.83M)
FEATURING ADAPTISHIFT™ WITH
UP TO 12" (30.5CM) OF OFFSET

CUT HEIGHT

0.37"-
2.75"
(9.5MM - 69.8MM)

CUTTING CAPACITY

4.5-5.3^{AC}
(1.83 - 2.13HA) / HR
(1.83-2.13M X 10KM /HR)

FUEL CAPACITY

7.6^{GAL}
(28.7L)

MOWER ENGINE

24.8HP
(18.6KW) DIESEL

BLADES PER REEL

5,7
OR **11**



JACOBSEN

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10016-G2 (Rev. 01/2025)

TR330

HIGH TRACTION SIDE SHIFTING TRIM MOWER



The TR330 eliminates the need for regular brake maintenance with wet parking brakes that are completely maintenance free.



This machine is built with operator comfort in mind, featuring an ergonomic design and easy-to-use controls in order to limit operator fatigue.



Available in 72-inches or 84-inches, the TR330's cutting width gives the flexibility to cut different areas with different settings.



330

DECKS & CUTTING UNITS

| | |
|-------------------|---|
| NUMBER AND SIZE | 3 x 26" (0.66m) or 30" (0.76m) reels; 7" (178mm) diameter |
| BLADE MATERIAL | Hardened, high manganese carbon steel |
| CUTTING UNIT LIFT | Armrest mounted joystick |
| CUTTING FREQUENCY | - |

TRACTION, BRAKES & SPEED

| | |
|------------------|--|
| TRACTION DRIVE | Parallel-series "on demand" 3WD |
| REEL DRIVE | Fixed displacement hydraulic |
| HYDRAULIC SYSTEM | 8.7 gal. (33L) capacity, full flow filtration (10 micron filter); GreensCare biodegradable oil |
| SERVICE BRAKES | Dynamic braking through hydrostatic drive |
| PARKING BRAKES | Service-free electronic wet disc |
| STEERING | Hydraulic power steering with tilt wheel |
| MOWING SPEED | 6.2mph (10km/h) |
| TRANSPORT SPEED | 8.7mph (14km/h) |

WEIGHTS & DIMENSIONS

| | |
|---------------------------------|------------------------------|
| WEIGHT (excluding fuel) | 1664 - 2299lb (755 - 1043kg) |
| LENGTH | 97" (2.46m) |
| OVERALL HEIGHT (including ROPS) | 80" (2.04m) |
| WHEELBASE | 43.5" (1.36m) |
| TRANSPORT WIDTH | 65.5" (1.66 m) |
| WORKING WIDTH | 83" (2.11m) |

WARRANTY

| | |
|----------------|---------|
| MOWER WARRANTY | 2 Years |
|----------------|---------|

ACCESSORIES

- Slick tires
- Verticutting reels
- Grass baskets
- Light kit
- Backlap kit
- Canopy
- Weight transfer kit



For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

